

D.I.Y 12Y SOLAR COLLUCIUS

STEP 1. SELECT SOLAR PANEL

	FIG. NO.	MODEL NO.	SOLAR PANEL	WATTS / VOLTAGE	DIMENSIONS (mm)	APPLICATIONS	SUITS SOLAR CONTROLLER
	1	KT70715		10W 12V	Length: 355mm Width: 225mm Depth: 17mm	Maintenance charging of 12V small sealed-lead acid batteries	Safe to use unregulated (without solar controller)
	2	KT70716		20W 12V	Length: 483mm Width: 343mm Depth: 17mm	Maintenance charging of 12V small sealed-lead acid batteries	8 AMP
	3	KT70717		40W 12V	Length: 420mm Width: 670mm Depth: 25mm	Maintenance charging of 12V small sealed-lead acid batteries	8 AMP
	4	KT70728		120W 12V	Length: 945mm Width: 670mm Depth: 35mm	Maintenance charging of 12V sealed-lead acid batteries	8 AMP or 10 AMP
5	5	KT70729		200W 12V	Length: 1476mm Width: 670mm Depth: 35mm	Maintenance charging of 12V sealed-lead acid batteries	20 AMP

STEP 2. SELECT SOLAR CONTROLLER

	EP 2.	SELECT.	JULAI	CONTROLLE	×
FIG. NO.	MODEL NO.	SOLAR CONTROLLER	AMPS / VOLTAGE	BATTERY COMPATIBILITY	SUITS SOLAR PANEL CAPACITY
7	KT70755	da tor room	8A / 12V	CHARGES SINGLE BATTERY GEL, WET, AGM, CALCIUM *NOT COMPATIBLE WITH LITHIUM	Suits Single Cell 12V Solar Panels up to 120W
2	KT70756	Edit Carlo	10A / 12V	CHARGES SINGLE BATTERY GEL, WET, AGM, CALCIUM & LITHIUM	Suits Single Cell 12V Solar Panels up to 150W
3	KT70757	Size of a lay control	20A / 12V	CHARGES SINGLE BATTERY GEL, WET, AGM, CALCIUM & LITHIUM	Single Cell 12V Solar Panel Maximum 200W or 2 x 150W Panels in Parallel
4	KT70762	SA ELY FIVM	15A / 12V DUAL	CHARGES 2 BATTERIES GEL, WET, AGM, CALCIUM & LITHIUM	Single Cell 12V Solar Panel Maximum 200W or 2 x 120W Panels in Parallel


STEP 3. SELECT POWER ACCESSORIES

91	EP 3	SELECT POWER	ACCES	SURIES
FIG. NO.	MODEL NO.	POWER ACCESSORY / LEAD TYPE	LEAD LENGTH (mm)	QTY REQUIRED
	KT70566	-97	600mm	1 Required
	KT70567	100 - 100 -	5M	Determine Length Required
2	KT70573		300mm	2 Required For Single Battery Systems 3 Required for 2 Battery Systems Use with Dual Charging Solar Controller
	KT70571		1М	1 Required For Single Battery Systems
3	KT70572		3М	2 Required for 2 Battery Systems Determine Length Required
4	KT70554	O POR STATE	300mm	1 Required For Single Battery Systems 2 Required for 2 Battery Systems

FOR PRODUCT DETAILS & OUR FULL KT SOLAR RANGE VISIT



GUIDE TO SETTING UP YOUR SOLAR SYSTEM



EG: FRIDGE / FREEZER
EG: LIGHTING
EG: AIR-COMPRESSOR
EG: LAPTOPS / PHONES
EG: INVERTER